

STAINLESS STEEL AISI316 PRESSURE SWITCHES

Applications:

711033 pressure switches are used to provide protection of industrial systems with corrosive media against unwanted pressures. They are also commonly used to protect compressors and fans when starting and stopping. The polycarbonate clear case allows the mechanism visualization. They can be connected to single-phase AC motors up to 2kW power, the switch incorporated is of the SPDT type. The housing has to be removed in order to modify the setpoint.

Technical data:

- Ambient temperature: -20-60°C
- Process temperature: -20+80°C
- Protection: IP66
- Cable entry: M20x1,5
- AC Load: 15 A
- DC Load: 5 A
- Accuracy: 1,5%

Materials

- Connection: AISI316
- Diaphragm: AISI316 (other materials are optional)
- Housing: clear polycarbonate



Model	Range [bar]		Differential*	Rearme	Switch	Connection
71103323	0,2	2,6	0,2	automatic	SPDT	1/4" GAS F
71103326	0,5	10	0,8	automatic	SPDT	1/4" GAS F

This publication does not try to establish the bases of a contract and the company keeps the right to modify without previous notice the design and the specifications of the instruments, in accordance with his politics of continued development.

MEI Manometría e Instrumentación, s.l.
Pol. Ind. "Gelidense" 3, nave 19 E-08790 Gelida Barcelona
Tf. +34 937 083 110 www.mei.es e-mail: comercial@mei.es