

DIGITAL PRESSURE GAUGE 655006 ACCURACY 0,1% WITH MAX-MIN FUNCTION

The 655006 is a compact digital pressure gauge that displays pressure in real time with high accuracy, equipped with a large 5-digit LCD display.

The pressure is measured 1 to 10 times per second (adjustable) and displayed. The display indicates the current pressure and temperature while the side indicates the unit of measurement.

The digital manometer 65500 has 6 keys. On/Off, Units, Zero, Up, Down and Light

Aplication:

Mainly used in petrochemical industry, water treatment, beverage equipment, pharmaceutical industry, processing and food machinery.

Characteristics:

AISI 304 stainless steel case, AISI 316 stainless steel connection, easy to wash and replace the battery, excellent anti-vibration and anti-impact design, excellent stability, 3 to 5 times longer service life than mechanical pressure gauges..

Especifications:

Ranges from vacuum to 1000 bar
Accuracy +/- 0.1% , on demand 0.05%
Working temperature -10 to + 50°C
Temperature compensation 0 - 40 °C
Battery life : 3,600 hours
Wetted parts in stainless steel AISI 316
Degree of protection box IP65, electrical EN 61326
Standard connection ¼" BSP, others on request
5-digit LCD display
Measuring medium: air or compatible liquid
Triple AA 3 V or USB battery
Net weight 260 gr (battery included)
Diameter 105 mm
Total height 155 mm
Total width 45 mm



Battery change:

Remove the back cover of the pressure gauge, disconnect the battery from its terminals, place the new battery in its hole, make sure that it is firmly placed and that the polarity is correct..

Esta publicación no pretende sentar las bases de un contrato y la empresa se reserva el derecho de modificar sin previo aviso el diseño y las especificaciones de los instrumentos, de acuerdo con su política de continuo desarrollo.

MEI Manometría e Instrumentación, s.l.

Pol. Ind. "Gelidense" 3, nave 19 E-08790 Gelida Barcelona

Tf. +34 937 083 110 Fax. +34 937 083 109 www.mei.es e-mail: comercial@mei.es